



ST200

240 VOLT HIGH FLOW DIESEL TRANSFER PUMP

The new high flow rotary vane dual diesel transfer pump is available as a pump only, or with handle and wheels or as an optional pump kit with and/or filter, meter and auto nozzle. Max flow rate up to 200 LPM.



ST2K7-10



ST2-10A



ST2EF-10



ST2KE-10A

ST200

New dual rotary vane diesel transfer pump is capable of flow rates up to 200 LPM. For diesel use only. Suit high flow contractor use or mining use. 2.5 bar max pressure. 1½" BSP inlet/outlet. Made in Italy.

STHW

Handle and wheel set to suit ST200.

ST2-10A

ST200 dual pump with 10mt x 1½" Hose, and A1298 1½" High flow auto nozzle. Diesel use only.

ST2K7-10

ST200 dual pump with K700 mechanical 1½" Flow meter, 10mt x 1½" Hose and A1298 1½" High flow auto nozzle. Diesel use only.

ST2EF-10

ST200 dual pump with EFHD-30050 high flow fuel filter, 10mt x 1½" Hose and A1298 1½" High flow auto nozzle. Diesel use only.

ST2KE-10A

ST200 dual pump with K700 mechanical flow meter, EFHD-30050 high flow fuel filter, 10mt x 1½" Hose and A1298 1½" High flow auto nozzle. Diesel use only.

ORDERING INFORMATION

ST200	240 volt dual rotary vane pump. 200 LPM.
STHW	Handle and wheel set to suit ST200.
ST2-10A	ST200 pump with 10mt hose and auto nozzle.
ST2K7-10	ST200 pump with K700 meter, 10mt hose and auto nozzle.
ST2EF-10	ST200 pump with EFHD-30050 filter, 10mt hose and auto nozzle.
ST2KE-10A	ST200 pump with K700 meter, EFHD-30050 filter, 10mt hose and auto nozzle.

HIGH FLOW SELF PRIMING DIESEL/WATER PUMP

ORDERING INFORMATION

EPMN50L	50mm self priming centrifugal pump with 2HP motor. 50mm suction/delivery ports. 350 LPM at 15mt head. For diesel and clean water transfer. Continuous duty rated. With built-in basket strainer. Viton seal. 240 volts.
EPMN50	50mm self priming centrifugal pump with 2HP motor. 240 volts. 50mm suction/delivery ports. 900 LPM at 5mt head. For diesel and clean water transfer. Continuous duty rated. With built-in basket strainer. Viton seal.
EPMN65	65mm self priming centrifugal pump with 5.5HP motor. 3 phase. 65mm suction/delivery ports. 1400 LPM at 9.5mt head. For diesel and clean water transfer. Continuous duty rated. With built-in basket strainer. Viton seal.

240 VOLT DIESEL/WATER PUMP

ORDERING INFORMATION

MN02	50mm Inlet/32mm Outlet centrifugal pump with 2HP motor. 240 volts. 200 LPM at 22.5mt head. NBR seals. For diesel and clean water use.
MN01	50mm Inlet/32mm Outlet centrifugal pump with 1.5HP motor. 240 volts. 200 LPM at 21mt head. NBR seals. For diesel and clean water use.



EPMN50



MN0