GEAR PUMPS ELECTRIC AND ENGINE POWERED

GEAR PUMP 240 VOLT

For bulk oil and diesel transfer. 240 volt motor mounted on base with pulleys and belt. Used by oil-lubricant merchants for filling drums or tanks. Teflon seal upgrade as an option. Note: By-pass valve must be fitted, if used with on-off valve on discharge



GC240-1

240 volt 1" BSP self priming cast iron gear pump with 1" BSP female ports. 1 HP motor. Complete mounted on base with pulleys, belt and guard. 50 LPM max flow rate. Graphite packing gland.

GC240-2

240 volt 1" BSP self priming cast iron gear pump with 1" BSP female ports. 2 HP motor. Complete mounted on base with pulleys, belt and guard. 50 LPM max flow rate. Graphite packing gland.



Options:

- Suction Spear custom.
- Suction hose assy with camlock coupling.

GC240-32-3

240 volt 1½" BSP self priming high flow cast iron gear pump with 1½" BSP female ports. 3 HP motor. Complete mounted on base with pulleys, belt and guard. 100 LPM max flow rate. Graphite packing gland.

 Delivery hose assy with variety of discharge spout nozzle configurations.



KC25

1" Cast iron gear pump with pulley

ORDERING INFORMATION	
KC20	¾" Gear pump with pulley.
KC25	1" Gear pump with pulley.
KC32	1¼" Gear pump with pulley.
KC50	2" Gear pump with pulley.

PETROL POWERED GEAR PUMPS

Petrol powered gear pump for bulk oils, paints, molasses and other compatible liquids. Cast iron construction with graphite packing gland and pulley drive. Pumps mounted on base belt driven with Honda petrol engines. Roll frame and camlocks shown are optional. Teflon seal upgrade as an option. Note: By-pass valve must be fitted if used with on-off valve on discharge.

GCH4

1" Cast iron gear pump powered by 4HP 6:1 Reduction Honda petrol engine. Recoil start. 1" BSP female ports. 55 LPM max when tested with water. Complete mounted on base with pulleys, belt and guard.

GCH₅

1" Cast iron gear pump powered by 5HP 6:1 Reduction Honda petrol engine. Same spec as GCH4.

GCH32

11/4" Cast iron gear pump powered by 9HP 6:1 Reduction Honda petrol engine. Recoil start. 11/4" BSP female ports. 100 LPM max when tested with water. Complete mounted on base with pulleys, belt and guard.



GC5094

2" Cast iron gear pump powered by 13HP 6:1 Reduction Honda petrol engine. Recoil start. 2" BSP female ports. 200 LPM max tested with water. Complete mounted on base with pulleys, belt and guard.

GCYD4.8

1" Cast iron gear pump with diesel driven 4.8HP Yanmar engine. 45 LPM max when tested with water.
1" BSP female ports.

GCYD10

 $11\!\!4\!\!''$ Cast iron gear pump with diesel driven 10HP Yanmar engine. 90 LPM when tested with water. $11\!\!4\!\!''$ BSP female ports.

ORDERING INFORMATION	
GC240-1	240 volt 1" 1HP Gear pump.
GC240-2	240 volt 1" 2HP Gear pump.
GC240-32-3	240 volt 1¼" 3HP gear pump.
GCH4	4HP Honda 1" Gear pump.
GCH5	5HP Honda 1" Gear pump.
GCH32	9HP Honda 1¼" Gear pump.
GC5094	13HP Honda 2" Gear pump.
GCYD4.8	4.8 HP Yanmar 1" Gear pump.
GCYD10	10HP Yanmar 1¼" Gear pump.