Oil/Lube Equipment

Fuel Equipment

12V/24V Diesel Pumps



DUAL VOLTAGE 12/24 Volt PUMP

Dual Voltage 12/24 Volt rotary vane self priming pump for diesel refuelling operations.

12 Volt = 35 LPM/24 Volt = 70 LPM flow rate.

Code	Description					
NM1224	Dual Voltage pump 12/24 Volt with cable and clamps. 35/70 LPM.					
NM1224M	Dual Voltage pump 12/24 Volt with 4 Mtr hose and manual nozzle.					
NM1224MA	Dual Voltage pump 12/24 Volt with 4 Mtr hose and auto shut off nozzle.					
NM1224SK	Dual Voltage pump 12/24 Volt with 4 Mtr hose, suction for 205lt drum and manual nozzle and nozzle holder					
NM1224SKA	Dual Voltage pump 12/24 Volt with 4 Mtr hose, suction for 205lt drum and auto shut off nozzle with swivel nozzle holder					

Features:

- Cast iron rotary vane pump.
- · Made in Europe.
- Internal pressure relief bypass valve.
- 12 Volt = 35 LPM flow rate at nozzle.
- 24 Volt = 70 LPM flow rate at nozzle.
- 1" BSP female ports.
- 30 minute duty cycle.
- 4 Mtr cable and clamps.
- · Diesel use only.



Technical Specification							
ELECTRICAL	12 Volt = 16 amp, 24 Volt = 25 amp.						
WEIGHT	8kg pump only.						

85 LPM 12 OR 24 Volt HIGH VOLUME DIESEL TRANSFER PUMP KITS



BP80SKA

Code	Description
BP80	12 Volt Pump with cable, clamps and fuse. 85 LPM max free flow.
BP80M	12 Volt Pump with 4 Mtr hose and manual nozzle. 80 LPM flow rate at nozzle.
BP80MA	$12\mbox{Volt}$ Pump with 4 Mtr hose and auto shut off nozzle. 75 LPM flow rate at the nozzle.
BP80SK	12 Volt high volume pump kit complete with manual nozzle, nozzle holder, 4 Mtr hose and suction for 205 Ltr Drum. 80 LPM at the nozzle.
BP80SKA	12 Volt high volume pump kit complete with auto shut off nozzle, swivel, nozzle holder, 4 Mtr hose and suction for 205 Ltr Drum. 75 LPM at the nozzle.
BP80V2	24 Volt Pump with cable, clamps and fuse. 85 LPM max free flow.
BP80V2M	$24\mbox{Volt}$ Pump, $4\mbox{Mtr}$ hose and manual nozzle. $80\mbox{LPM}$ max flow rate at the nozzle.
BP80V2MA	24 Volt Pump, 4 Mtr hose and auto shut off nozzle. 75 LPM at the nozzle.
BP80V2SK	24 Volt high volume pump kit complete with manual nozzle, nozzle holder, 4 Mtr hose and suction for 205 Ltr Drum. 80 LPM flow at nozzle.
BP80V2SKA	24 Volt high volume pump kit complete with auto shut off nozzle, swivel, nozzle holder, 4 Mtr hose and suction for 205 Ltr Drum. 75

85 LPM 12 Volt Diesel Pump Kits for volume refuelling operations with large equipment. Excellent for auto nozzle volume flows. Used in fuel trailers, stationary or mobile tanks, trucks or utes.

Features:

- Cast iron rotary vane pump.
- Internal pressure relief bypass valve.
- 30 minute duty cycle.
- 85 LPM max free flow.
- 4 Mtr cable and clamps.
- · European made.

Options:

- Meter.
- Fuel filter.
- · Base mount.
- Extra hose length.

Technic	al Spe	ecifica	ation						
ELECTR	ICAL		12 Volt = 50 amp, 24 Volt = 20 amp.						
H(m)									
20									
18									
16									
14			\rightarrow	_					
12 —				$\overline{}$					
10					$\overline{}$				
8 —						$\overline{}$			
6						\rightarrow			
4				80 L	DM		$\overline{}$		
2				- OO L	1*1		\rightarrow		
0	1.0							<u>\</u>	
0	10	20	30	40	50	60	70	80 90	