

### 1.0% TANK GAUGE

- 1% Tank gauge kit with high and low audible alarm.
- Suitable for tanks 0.3 Metres to 3.0 Metres high with diesel and 0.3 to 2.5 Metres high with Adblue.
- 24 Volt DC or 100/240 Volt AC supply.
- 1" Tank connection. Sensor cable is 6 Metres long. Includes 4 - 20mA output.



Code	Description
TG2-PRO	1% Tank gauge kit with high and low audible alarm

### 0.25% TANK GAUGE KIT

A unique programmable Tank Gauge Unit with local display. Ability to input a strapping table or calibrate to exact tank dimensions.

#### Outputs:

Dependent upon your requirement, the TG5 can provide:  
Linear 4-20 mA output from nonlinear input.

#### Alarm Functions

4 x Programmable alarm/ trigger set-points, (see outputs).  
e.g. High Level Local alarm with acknowledge circuit.

#### Enclosure

IP65 Fully weatherproof for outdoor use.

#### Cable connections

Weatherproof cable glands are provided for power supply and signal inputs. Screw down & plug in Terminal strips are provided within the enclosure

#### Accuracy

- +/- 0.25%.

Operating Temperature: -5 to +60 DegC

Humidity: 5 to 95%



TG5-ELITE

Code	Description
TG5-ELITE	Tank gauge kit. 0-3 Metre ranged probe, suit tanks 1.8 to 3.5 Metres in diesel. Includes software installation kit. 240 Volt.

### WEB LOGGER

#### + GPRS Web Viewer

A unique web programmable Monitor Unit. 240 Volt AC.  
Any 24vdc 4-20 mA output can be monitored and scaled by this simple monitor.

#### Connects directly to

TG2-PRO 1% Tank Gauge

TG5-ELITE 1/4% Tank Gauge

or any Instrument giving a 4-20 milliamp output signal.

#### Web Features

30 minute logging provides 48 level samples per day. The web site has e-mail trigger set point for re-order as well as a leak / theft \*detection monitor. Exception reporting,



TG-WWW

Code	Description
TG-WWW	Web logger - 240 Volt
W-3GAU	Web logger 3G plan