

HUSKY AUTOMATIC SHUTOFF NOZZLES



HS45

- Husky automatic shut off nozzle for petrol.
- ¾" BSP female inlet.
- NMI approved for retail use.
- 45 LPM Max flow rate.
- Made in USA.
- Fitted with Flo-Stop™ device shuts off nozzle if it falls from fill neck or when raised above horizontal.
- Dual poppet design for easier opening of nozzle.
- Pump use only



HS100

- Husky automatic shut off nozzle for diesel.
- 100 LPM Max flow rate.
- 1" BSP female inlet – 24mm O.D outlet spout.
- NMI approved for retail use.
- Made in USA.
- Fitted with Flo-Stop™ device shuts off nozzle if it falls from fill neck or when raised above horizontal.
- Dual poppet design for easier opening of nozzle.
- Nozzle comes standard with full grip guard and splash guard.
- Aluminium body construction.
- Includes hold open adjustable trigger clip.
- Pump / Diesel use only.



HS68

- ¾" BSP husky automatic shut off Service Station Bowser Nozzles
- NMI approved for retail use.
- 68 LPM max flow rate.
- Made in USA.
- Flo-stop™ device that shuts off nozzle in event that nozzle falls or is raised above horizontal
- Pump / Diesel use only



HS280

- 1" BSP female inlet.
- NMI approved for diesel retail use.
- High flow diesel truck stop nozzle
- Made in USA.
- Heavy duty for all rigours of retail or commercial fleet users
- 275 LPM max flow
- Flo-Stop™ device
- Pump / Diesel use only

HS380

- Automatic high flow refuelling nozzle
- Maximum flow rate: 375 Litres per minute
- Inlet: 1½" F BSP
- Durable die cast aluminium nozzle body.
- Pump / Diesel use only
- Made in USA.



Code	Description
HS45	¾" Husky automatic yellow unleaded nozzle. 45 LPM max.
HS68	¾" Husky automatic shut off Service Station Bowser Nozzles for diesel. 68 LPM max.
HS100	1" Medium flow Husky diesel auto shut off nozzle. 100 LPM max.
HS280	1" Husky automatic shut off Service Station Bowser Nozzle for diesel. 275 LPM max.
HS380	1½" Automatic high volume heavy duty nozzle. 375 LPM max.