

ELECTRIC AND AIR OPERATED PUMPS FOR NEW AND WASTE OIL

Equipco range of waste oil pumps are used for a wide variety of industry requirements. ITALIAN MADE.

12 & 24 VOLT



G212B



NM4506



DP41WM



KP41NKOE

KP41NKOEHDT

ORDERING INFORMATION

G212B	12 volt Italian made self priming bronze gear pump for use with some viscous liquids, lubricants and waste oil. Bronze housing. 10 LPM max flow. 50 PSI max pressure. 3/8" BSP ports. 30 minute duty cycle. In-built bypass. Complete with cable and clamps.
G224B	24 volt Italian made self priming bronze gear pump for use with some viscous liquids, lubricants and waste oil. Bronze housing. 10 LPM max flow. 50 PSI max pressure. 3/8" BSP ports. 30 minute duty cycle. In-built bypass. Complete with cable and clamps.

240 VOLT - ITALIAN MADE

ORDERING INFORMATION

NM4506	240 volt Italian made self priming bronze gear pump for use with some viscous liquids, lubricants and waste oil. 10 LPM max flow. 50 PSI max pressure. 3/8" BSP ports. Continuous use. Motor equipped with thermal protection. Bronze housing. In-built bypass.
--------	---

AIR OPERATED - EUROPEAN MADE

ORDERING INFORMATION

DP41WM	The Faicom DP41WM air operated pump is designed for transferring waste oil and anti-freeze. Pump must be fitted with a fine suction strainer when in use with waste oil. 4:1 ratio. 22 LPM max flow.
KP41NKOE	Waste oil Faicom suction wall mount bracket kit which is designed for sucking oil from engine through the dipstick by flexible probes. Kit includes wall mount steel panel, DP41WM pump, probes, hose and suction valve, y line filter and vacuum gauge. 7-9 LPM flow.
KP41NKOEHDT	Same as KP41NKOE but with 7mt 1/2" Hose reel and drip tray. 6-8 LPM flow.

SUBMERSIBLE PUMPS

Equipco supply a range of submersible pump sizes to suit options with diesel, sea water and water transfer.

Options:

- Suction strainer.



12TENK



12TEN-410A



12TEN-410A

ORDERING INFORMATION

12TENK	12 volt submersible transfer pump for diesel and fresh water. 50mm dia. 40 LPM max free flow. 30 minute duty cycle max. 3/4" Hose tail connection. Approx. 500-600 hours pump life.
12TEN-410A	12 volt submersible transfer pump kit. Complete with 4m rubber hose, manual nozzle and fittings. For diesel or fresh water. 30 LPM max.
24TENK	24 volt submersible transfer pump for diesel and fresh water. 50mm dia. 40 LPM max free flow. 30 minute duty cycle max. 3/4" Hose tail connection. Approx. 500-600 hours pump life.
24TEN-410A	24 volt submersible transfer pump kit. Complete with 4m rubber hose, manual nozzle and fittings. For diesel or fresh water. 30 LPM max.
LVM105	Amazon 12 volt pump. 1/2" Connection. 150 hour brush life. 15 LPM. Temp up to 80°C with water. Fits inside 2" Fill pipe on fuel tank. 9mt head max. Salt water or diesel use only. Can also be used as an inline pump.
LVM117	Amazon 24 volt pump. 1/2" Connection hose barb. 150 hour brush life. 10-15 LPM. Temp up to 80°C with water. Fits inside 2" Fill pipe on fuel tank. 9mt head max. Salt water or diesel use only.