FILLRITE IECEX APPROVED FLAMMABLE METER FOR PETROL, DIESEL AND JET-A1



www.equipco.com.au 1800 813 182

• 1" BSP Fillrite IECEx approved

USA

nozzles.

digital display.

• 8 - 132 LPM flow rate

• Suitable for use with

flammable turbine meter - made in

· UL listed made from Aluminium with

· For use as a inline meter at end of

Petrol, Diesel, Jet-A1 and Kerosene.

Accurate within 1%, this turbine meter sets the standard for accuracy, ease of use and safety. It has factory presets for 20 fluids and UL/ATEX listing on the entire meter, not just the electronics as competing brands have. Replaceable AA batteries keep your meter running and downtime to a minimum. A rubber boot helps protect the meter and electronics from impact damage.

- Install it where you need it, even at the end of the hose.
- Measure gallons, litres, quarts, pints, and ounces with one meter.
- A priority on safety with intrinsically safe electronics and near global regulatory approvals provide peace-of-mind.

TT10EX


























	I I IUEX
Flow Rate (GPM/LPM)	2-35 / 8-132
UL Max Pressure (psi)	50 PSI (3.4 Bar)MAX UL. 300 PSI (20.7 Bar) Burst
Operating Temp (°F/°C)	-40°F-176°F / -40°C-60°C
Meter Const	Aluminum
Inlet/Outlet	1" BSPP
Meter Accuracy	+/- 1.00%
Meter Dimensions	4" W x 2.6" D x 2.9" H
Units of Measure	Ounces, pints, quarts, liters, or gallons
Power Source	2 AA Batteries
Meter Weight (oz/g)	15 / 425
Certifications	cULus, CE, ATEX, IECEx
Compatible Fluids	Gasoline, Diesel, Jet Fuel, Heptane, Kerosene, Mineral Spirits
Retail Pkg Dimensions	6.5" W x 3.1" D x 8.9" H
Retail Pkg Weight (oz/g)	19 / 539
Product UPC	089404226292