

# AUTOMATIC FUEL DISPENSING NOZZLES

Photo is A120L-SW model



## AUTO NOZZLES

Scuff guard. 40-200LPM. Pump use only.

<b>A60</b>	3/4" Diesel nozzle. 60 LPM max.
<b>A60-SW</b>	3/4" Diesel nozzle with swivel. 60 LPM
<b>A60-NL</b>	3/4" Unleaded petrol nozzle. 40 LPM
<b>A120L</b>	1" Auto Diesel nozzle. 200 LPM
<b>A120L-SW</b>	1" Auto Diesel nozzle with swivel. 200 LPM

The Equipco range of automatic nozzles offer a broad range of flow rates to meet most applications for auto-shut off refuelling.

## THE NOZZLES COME STANDARD WITH BSP INLET THREADS

The light weight, single body sand cast aluminium construction produces a smooth working rugged nozzle specifically designed for endurance.

### A60

- 3/4" BSP Inlet.
- One-hand hold open mechanism for effortless operation.
- Full scuff guard.
- Spout is easily replaced on location.
- Weight 1.1 kg.
- Pump use only.
- 60 LPM max - A60.
- 40 LPM max - A60-NL.
- 25 PSI W.P.

### A120L

- Heavy duty high flow truck stop nozzle for the rigours of diesel refuelling. Compact, strong lightweight construction.
- 1" BSP Inlet.
- Scuff guard.
- Spout is easily replaced on location.
- 200 LPM max.
- Weight 1.55 kg.
- Pump use only.
- 25 PSI W.P.