DIESELSTOR CUBE TANKS



SPECIFICATION

✓ Design

Self-bunded double wall all steel fuel tank.

Tank Base Assembly

Heavy duty construction. Tank floor is raised off the ground.

Static Tank

The DSC Series is a static tank. For transportable tanks ask for MGSeries MineGo tanks.

✓ Forklift Compatability

Equipped with forklift pockets to each side capable of handling and moving whilst full of diesel, except for the model MG5000N.

Fill Connection

2" fill point & 2" dip point, inside lockable spill pan with overflow into bund.

✓ Vent

Fitted with 2" air vent and riser pipe.

Approvals & Compliance

AS1692-2006 & AS1940-2004.

Paint finish

All external surfaces are sand blasted and coated with a high-quality 3 coat marine paint system.

✓ Dip Stick

Supplied with incremented dip stick

Access Cover(s)

One inspection accesshole for inspection of the inner tank

Connection Sockets

One (1) x 1 1/2" BSP & three (3) x 1" BSP pump suctions, and three (3) 1" BSP return sockets inside pump bay.

Feed & Return

Capable of connecting up to three (3) generators. Options available for feed & return hoses with quick connect couplings.

Pump Bay

Secure & lockable access hatch to house pump and feed & return connections for up to three (3) generators.

Signage

All statutory signage supplied for fuel.

✓ Stackable

Easily stacked two (2) high empty. Sized to stack inside shipping containers and across truck beds providing economical transportation.













DESIGNED FOR POWER-GEN AND CONTRACTOR USE FOR STORAGE OF DIESEL FUEL.

ALL IN A COMPACT RUGGED DESIGN FOR EASE OF USE IN MULTIPLE APPLICATIONS

- Designed for Power-Gen and contractor use for storage of diesel fuel, static storage.
- Complete with pump compartment, fill and suction- return points for generator feed for up to 3 units.
- All in a compact rugged design for ease of use in multiple applications.
- Optional Flammable kit for Petrol static storage available at additional cost.
- Optional Pump Kits available

Model	Safe Fill Litres	Usage	Length mm	Width mm	Height mm	Weight Empty kg
DSC1000N-C	1000	Diesel	1530	1150	1290	510
DSC2000N-C	2000	Diesel	2240	1340	1350	880
DSC3000N-C	3000	Diesel	2240	1950	1350	1180
DSC5000N-C	5000	Diesel	3027	2270	1214	1850
DSC1000N-F	1000	Petrol	1530	1150	1290	510
DSC2000N-F	2000	Petrol	2240	1340	1350	880
DSC3000N-F	3000	Petrol	2240	1950	1350	1180
DSC5000N-F	5000	Petrol	3027	2270	1214	1850