

# EFHD FUEL FILTERS

Gravity flow or pump applications with bulk storage tanks in many industrial applications. The EFHD series filters enable flows up to 300 LPM with Working Pressure max. 50 PSI.

There are multiple element options available for a range of applications



Mounting bolt holes on 25mm head

Easy spin/off canister design allows for easy replacement of old/damaged canisters

Large body canisters for longer overall element life and higher flow allowance

## DESIGNED TO MOUNT ON LARGE OVERHEAD STORAGE TANKS OR PUMPS

### PARTICLE FILTER ASSEMBLIES

Code	Size	Micron	Pressure Max	Flow Rate	Fluids
EFHD-9010-25	1" BSP	10 micron	50 PSI	94 LPM	Diesel, petrol, ethanol and methanal blends up to 10%.
EFHD-1502-25	1" BSP	2 micron	50 PSI	150 LPM	Diesel, petrol, ULSD and biodiesel
EFHD-1502-40	1½" BSP	2 micron	50 PSI	151 LPM	Diesel, petrol, ULSD and biodiesel
EFHD-15010-25	1" BSP	10 micron	50 PSI	151 LPM	Diesel, petrol, ULSD and biodiesel
EFHD-15010-40	1½" BSP	10 micron	50 PSI	151 LPM	Diesel, petrol, ULSD and biodiesel
EFHD-3002-50	2" NPT	2 micron	50 PSI	300 LPM	Diesel, petrol, ULSD and biodiesel
EFHD-30010-50	2" NPT	10 micron	50 PSI	302 LPM	Diesel, petrol, ULSD and biodiesel

### WATER ABSORBING AND PARTICLE FILTER ASSEMBLIES

Code	Size	Micron	Pressure Max	Flow Rate	Fluids
EFHD-9010W-25	1" BSP	10 micron water absorbing	50 PSI	94 LPM	Diesel, petrol, ethanol and methanal blends up to 10%
EFHD-1502W-25	1" BSP	2 micron water absorbing	50 PSI	151 LPM	Diesel, petrol, ULSD and biodiesel
EFHD-1502W-40	1½" BSP	2 micron water absorbing	50 PSI	151 LPM	Diesel, petrol, ULSD and biodiesel
EFHD-15010W-25	1" BSP	10 micron water absorbing	50 PSI	151 LPM	Diesel, petrol, ULSD and biodiesel
EFHD-15010W-40	1½" BSP	10 micron water absorbing	50 PSI	151 LPM	Diesel, petrol, ULSD and biodiesel
EFHD-3002W-50	2" NPT	2 micron water absorbing	50 PSI	302 LPM	Diesel, petrol, ULSD and biodiesel
EFHD-30010W-50	2" NPT	10 micron water absorbing	50 PSI	302 LPM	Diesel, petrol, ULSD and biodiesel

### REPLACEMENT ELEMENTS

Code	Element	Micron	Pressure Max	Flow Rate	Fluids
EFHD-9010	70034	10 micron	50 PSI	94 LPM	Diesel, petrol, ethanol and methanal blends up to 10%. Particulate.
EFHD-9010W	70075	10 micron water block	50 PSI	94 LPM	Diesel, petrol, ethanol and methanal blends up to 10%. Hydrosorb.
EFHD-1502W	70037	2 micron water block	50 PSI	151 LPM	Diesel, petrol, ULSD and biodiesel use. Hydroglass.
EFHD-15010	70019	10 micron	50 PSI	151 LPM	Diesel, petrol, ULSD, biodiesel use, Ethanol or methanol blends up to 15%. Particulate.
EFHD-15010W	70063	10 micron water block	50 PSI	151 LPM	Diesel, petrol, ULSD and biodiesel use. Hydrosorb.
EFHD-1501B	70041	1 micron Hydroglass	50 PSI	151 LPM	Petrol, ethanol blends up to E85, biodiesel (B100), ULSD and methanol (M100). Microglass.
EFHD-150144M	70080	144 micron mesh	50 PSI	150 LPM	Diesel, petrol, ULSD, ethanol blends up to 15%, and bio-diesel blends up to B20