

# FUELINE™ PUMP HOSE



FOR DIESEL & PETROL



## WITH AS2683-2000 / TYPE2 / WP 1500 KPA / GRADE 2 / KIND 1 APPROVALS

Designed for pump fit outs, Equipcos FUELINE PUMP HOSE meets AS268-2000 to give you peace of mind in your important refuelling jobs. Designed specifically for pump applications, this hose meets all the requirements for fitting at a retail bowser. Available for both Diesel and Petrol, both varieties are made from an NBR carbon blend with a high tensile synthetic braid. The hose is available in 20, 40 and 60 metre coils.

### Details on AS2683-2000

Specifies requirements for hose and hose assemblies for conveying petroleum and petroleum products, except for liquefied petroleum gas, at product temperatures up to 65C in ambient temperatures ranging from -20C to 55C. Intended for hose applications involving road and rail tankers, metered pumps, farm tanks, reeling, aviation and general plant operations.

- Antistatic rubber hose with conductive wire, two types available for use with petrol or diesel pumps.
- Meets all approvals for use for petrol and diesel dispensing at service stations, mine sites and industry specified applications.
- NBR Carbon blend with high tensile synthetic braid.
- AS2683-2000 Approved
- FLDH25 Diesel hose rated to 145 PSI max W.P
- FLPH25A Petrol hose rated to 215 PSI max W.P

Available in 20M/40M/60M coils

### Specifications

FLDH25	FUELINE™ Diesel Pump Hose 1" I.D with AS2683-2000 / Type1 / WP 1000 KPA / Grade 2 / Kind 1 approvals
FLPH25A	FUELINE™ Petrol Pump Hose 1" I.D with AS2683-2000 / Type2 / WP 1500 KPA / Grade 2 / Kind 1 + 2 approvals