

FUEL DELIVERY HOSE - DIESEL/ PETROL



FOR DIESEL, PETROL AND OIL

HIGH GRADE RUBBER DISPENSING HOSE FOR MANY PETROLEUM PRODUCTS

A staple of our product offerings for years, the Equipco MF hose is well trusted by many of our customers. With an anti-static wire running through the hose and constructed from an NBR carbon blend, the hose is well suited for diesel, oil and petrol. Rated to 150PSI, it's suited for a wide range of pumps as well as gravity feeds. We stock this hose in both 3/4" and 1" I.D.s, with 20mt, 40mt and 60mt coils on offer as well as custom cut lengths.

- 150 PSI max W.P. Conductive tube with anti-static wire For pump or gravity applications. Suits diesel/unleaded petrol fuel
- NBR carbon blend inner tube with anti-static wire
- Robust fuel transfer hose for use with diesel and petrol fuels up to 55% aromatic content. Long life durable hose. Smooth extruded rubber tube and cover with fabric braid.

Specifications

Available in 20M/40M/60M coils

MF-020	19mm (3/4") I.D. 27.5mm O.D. Rubber fuel delivery hose for pump or gravity applications. 150 PSI W.P. Suitable for use with diesel or petrol up to 55% aromatics.
MF-025	25mm (1") I.D. 35mm O.D. Rubber fuel delivery hose for pump or gravity applications. 150 PSI W.P. Suitable for use with diesel or petrol up to 55% aromatics.



Code	SIZE	WORKING PRESSURE	SAFETY FACTOR	BURSTING PRESSURE	TUBE COMPOUND	COVER COMPOUND	EXTERIOR	REINFORCEMENT	TEMPERATURE RATING	REMARKS
MF-025	1" X 35.5MM	150 PSI	3:1	450 PSI	NBR BLENDED	NBR / PVC BLENDED	BLACK, EXTRUSION - SMOOTH SURFACE	POLYESTER YARN	-20°C~ +70 °C	EMBEDDED WITH ONE (1) ANTI-STATIC WIRE