FUELINETM REELING HOSE









HIGH GRADE RUBBER DISPENSING HOSE FOR MANY PETROLEUM PRODUCTS

Designed for use on reels, Equipco's FUELINETM REELING HOSE meets AS2683-2000 to give you peace of mind in your important refuelling jobs. Available in 1", 1-1/4" and 1-1/2", this high grade rubber hose is well suited for heavy duty truck reel installs. With a conductive inner and outer tube as well as an antistatic wire running through the hose, it's suited for both petrol and diesel transfer. This hose is available in full coils of 30mt or custom cut lengths.

Details on AS2683-2000

Specifies requirements for hose and hose assemblies for conveying petroleum and petroleum products, except for liquefied petroleum gas, at product temperatures up to 65C in ambient temperatures ranging from -20C to 55C. Intended for hose applications involving road and rail tankers, metered pumps, farm tanks, reeling, aviation and general plant operations.

- FUELINE™ Reeling Hose for diesel, petrol and oil.
- Includes conductive inner and outer tube with anti static wire.
- High grade rubber dispensing hose for many petroleum products.
- Mandrel built hose with wrapped finish.
- 290 PSI max W.P
- AS2683-2000 approved.

S	ne	cif	ica	atio	ns
_	μc	CII	100	2010	/112

Available in 30M coils

PRP25P	FUELINE™ Reeling Hose 1" (25mm) I.D with AS2683-2000 / Type2 / WP 2000 KPA / Grade 2 / Kind 1 + 2 Approvals	
PRP32P	FUELINE™ Reeling Hose 1 1/4" (32mm) I.D with AS2683-2000 / Type2 / WP 2000 KPA / Grade 2 / Kind 1 + 2 Approvals	
PRP40P	FUELINE™ Reeling Hose 1 1/2" (40mm) I.D with AS2683-2000 / Type2 / WP 2000 KPA / Grade 2 / Kind 1 + 2 Approvals	